

Rail Drilling Machine TFR 130 P SAFE 5952000 MM-205-03



- Lightweight. 17,8 kg
- Easy clamp system
- Quick rail profile changing
- 330 RPM
- Adjustable hole centre locator
- Easy Tram clamp attachment

The SAFETRACK TFR 130 P rail drilling machine is a lightweight and easily manoeuvrable machine. It is equipped with a 4-stroke Honda engine and it is able to drill, quickly and accurately, any vignola and tram rails.

Even power distribution

The advancing lever of the crown cutter is directly connected to the engine. This system allows to use only the power which in that moment is necessary for the perforation, limiting the usury of the tool and fuel waste.

Used with Safetrack Super Drilling Paste (no need for cooling fluid) or with cooling fluid from the tank.

The quick fixing on the rail, the action of the fully protected tool and its balanced handle with safety switch, ensure minimal effort and maximum operator safety.

Drilling time approximately 20 to 60 seconds, depending of diameter of the hole and hardness of the rail.



Safetrack
Super Drilling Paste
SAFE 59579



See www.safetrack.se for special rail drill bits

Rail Drilling Machine TFR 130 P SAFE 5952000
Delivered as included with clamp system for vignol rail
Add necessary options below:

Accessories

Clamp system for Tram rail SAFE 5952050

Profile templates for rail size:

rails 43 / 50	SAFE 5952055
rails 50 / 60	SAFE 5952060
rails 49 / 54	SAFE 5952065
Tram rail 57R1 (PH37)	SAFE 5952105
Hole centre locator, 4 hole Vignol	SAFE 5952080
Hole centre locator, 4 hole Tram	SAFE 5952090
Super Drilling Paste	SAFE 59579

Technical Specification

Honda Engine, kW	1,5
Drill rotation speed, rpm	330
Hole diameter range, mm	up to 38
Drill bit length, mm	30 mm
Noise level during cutting, dbA	LwA 90 - LpA 83
Vibration magnitude, m/s ²	3,5

Dimensions: [l x w x h], mm	552x341x395
Dry weight, kg	17,8

SAFETRACK Baavhammar AB

Möllebergavägen 339-24, 245 93 Staffanstorp, Sweden

Tel. +46 (0)40 44 53 00 Fax. +46 (0)40 44 55 53

www.safetrack.se sales@safetrack.se